



# Aral Turboral Gas 15W-40

## Gas Engine Oil

### Description

High performance engine oil specially designed for gas fuelled engines (LPG or CNG) sensitive to the formation of deposits on the piston crown.

- Contains advanced anti-wear additives to protect against engine wear
- Advanced engine cleanliness

### Typical Characteristics

Name	Method	Units	Aral Turboral Gas 15W-40
Density @ 15C, Relative	ASTM D1298	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	13.7
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	102
Viscosity Index	ASTM D2270	None	135
Ash, Sulphated	ASTM D874	% wt	0.8
Pour Point	ASTM D97	°C	-30
Flash Point, COC	ASTM D92	°C	236

### Product Performance Claims

MB-Freigabe 226.9

DAF HP Gas

MAN 3271

RVI RGD

Volvo CNG

### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Turboral Gas 15W-40

24 Jul 2012

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de