



Aral Getriebeöl ATF E-S

Fully synthetic automatic transmission fluid

Description

Fully synthetic automatic transmission fluid according to GM specification ATF Type II E.

- Enables extended drain intervals for MB- and ZF- gearboxes

Typical Characteristics

Name	Method	Units	Aral Getriebeöl ATF E-S
Density 15 °C	DIN 51757	g/ml	0,840
Flash Point, PMCC	ASTM D93	°C	190
Pour Point	ASTM D97	°C	-51
Viscosity 100 °C	DIN 51562	mm ² /s	7,5
Viscosity 40 °C	DIN 51562	mm ² /s	31

Product Performance Claims

MAN 339 Z2, V2
Voith H55.6336.xx
ZF TE-ML 04D, 09X, 14B*, 16L
MB Approval 236.8

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Getriebeöl ATF E-S
20 Jan 2014

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg
01801-11 55 11
www.aral-lubricants.de