

Aral Fluid HGS 80W

Universal Transmission Fluid - UTTO



Description

Aral Fluid HGS 80W is designed for use hydraulic, transmission and PTO of tractors and off-highway equipment. It gives highest levels of wear prevention from start up and throughout the operative period with enhanced corrosion protection properties. One oil reduces inventory, simplifies serviceing, avoids misapplication and saves money.

Advantages

- Excellent oxidation stability and anti corrosion and anti wear properties
- Balanced temperature / viscosity profile ensures smooth gear shifting
- Excellent wet clutches and wet brake performance

Typical Characteristics

Name	Method	Units	Aral Fluid HGS 80W
Density @ 15C, Relative	ASTM D1298	g/ml	0.888
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	57
Viscosity Index	ASTM D2270	None	167
Pour Point	ASTM D97	°C	-39
Flash Point, COC	ASTM D92	°C	232

Product Performance Claims

API GL-4

Approved - ZF TE-ML 21F, 17E, 05F, 03E, Volvo 97303 (WB 101), MFM1145

Meets - Ford ESN-M2C-134D, John Deere J20C

Suitable for use where Case 1207, Case 1209, MAT 3505, MAT 3525, MAT 3540, NH410B or Ford M2C86-B are specified.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Fluid HGS 80W

11 Apr 2018

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de