

Aral MegaTurboral 10W-40

Premium heavy duty Diesel engine oil



Description

Aral MegaTurboral with XMF® technology is an Heavy Duty Engine oil developed especially for extended drains in the latest Euro 6 standard diesel engines.

Application

The minimized content of sulphated ash, phosphorus and Sulfur (Low SAPS Oil) makes Aral MegaTurboral the ideal partner for the most modern engines with exhaust aftertreatment.

Advantages

Aral "eXTra Motorschutz Formel" XMF® technology makes Aral MegaTurboral 10W-40 more resilient and notably reduces piston deposits and related abrasion. Engines are kept cleaner and wear is reduced.

Aral "eXTra Motorschutz Formel" XMF® technology performs up to 30% better in reducing the build-up of deposits and related wear.*

*Compared to API and ACEA industry requirements.

Typical Characteristics

Name	Method	Units	MegaTurboral 10W-40
Density @ 15C	ASTM D4052	g/ml	0.868
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.8
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6100
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	98
Ash, Sulphated	ASTM D874	% wt	1.83
Total Base Number, TBN	ASTM D2896	mg KOH/g	12.7
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	211

Product Performance Claims

ACEA E4, E7
API CI-4
JASO DH-1
Cummins CES 20077, CES 20078
DDC Powerguard 93K215
Deutz DQC III-18
DTFR 15B120 (MB 228.5)
Mack EO-N
MAN M 3277
MTU Oil Category 3
RVI RLD-2
Volvo VDS-3

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral MegaTurboral 10W-40
26 Feb 2024
Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg
01801-11 55 11
www.aral-lubricants.de