

Aral Getriebeoel ATF LD

Fully Synthetic Automatic Transmission Fluid



Description

Aral Getriebeoel ATF LD is a high quality full synthetic transmission fluid. It is particularly recommended for use in automatic and semi automatic transmissions used in buses and coaches. It may also be used in manual transmissions. As such it is recommended for fleets employing a mixture of Voith, Renk, ZF, Allison and MB transmissions alongside the Leyland Pneumocyclic and Hydracyclic units. Extended oil drain [120.000 km] in ZF Ecomat, MB AT and Voith AT.

Advantages

- Excellent resistance to oxidation prolonging the life of the lubricant, offers extended drain potential and lowers operating costs.
- Enhanced protection against deposits extends transmission life.
- Temperature reduction in severe service improves transmission and oil service life and helps reduce fuel consumption and emissions.
- Optimised frictional characteristics providing smoother gear changes and protects against wear.
- Outstanding cold flow properties giving high protection to transmission especially at start-up

Typical Characteristics

Name	Method	Units	Getriebeoel ATF LD
Density @ 15C, Relative	ASTM D4052	g/ml	0.836
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	37.8
Viscosity Index	ASTM D2270	None	170
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	8400
Pour Point	ASTM D97	°C	-66
Flash Point, COC	ASTM D92	°C	228

Product Performance Claims

ZF TE-ML 04D, 11B, 14C, 16M, 16S, 20C, 25C
MAN 339 Typ Z3, MAN 339 Typ Z12, MAN 339 Typ V2
Voith H55.6336.xx
MB-Approval 236.81

Additional Information

Getriebeöl ATF LD is registered under the following ZF approval numbers: ZF000144

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Getriebeoel ATF LD

23 Oct 2019

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

www.aral-lubricants.de