

# Aral SuperTurboral LA 5W-30

Low SAPS engine oil for latest European diesel engines



## Description

Aral SuperTurboral LA is a 5W-30 heavy duty diesel engine oil designed to allow fleet operators to run their new vehicles to extended oil drain intervals. \*Low SAPS" means that the lubricant is formulated with lower levels of Sulphated Ash, Phosphorus and Sulphur than conventional oils. Aral SuperTurboral LA 5W-30 uses unique additive technology to provide excellent engine protection for Euro 4,5 & Euro 6 vehicles when used at extended oil drain intervals, even under severe operating conditions.

## Advantages

- Excellent low temperature characteristics ensure the oil circulates quickly to all moving parts of the engine also under cold start conditions.
- Extended oil drain intervals to keep vehicles on the road for longer. The unique low SAPS additive system keeps on working even in the toughest conditions.
- OEMs have approved Aral SuperTurboral LA 5W-30 for use at their extended oil drain intervals.
- Aral SuperTurboral LA 5W-30 maintains the efficiency of exhaust after-treatment systems ensuring continued compliance with emissions legislation

## Typical Characteristics

Name	Method	Units	Aral SuperTurboral LA 5W-30
Density @ 15C	ASTM D4052	g/ml	0.854
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	11.8
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	6100
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	69
Viscosity Index	ASTM D2270	None	166
Ash, Sulphated	ASTM D874	% wt	0.99
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.45
Pour Point	ASTM D97	°C	-48
Flash Point, PMCC	ASTM D93	°C	200

## Product Performance Claims

ACEA E6, E7, E9  
API CJ-4  
JASO DH-2  
CAT ECF-3  
Cummins CES 20081  
Deutz DQC IV-10LA  
Mack EO-M Plus, EO-N, EO-O Premium Plus  
MAN M 3677  
MB-Approval 228.51  
MTU Oil Category 3.1  
RVI RLD-2 RLD-3 RXD  
Scania LDF-4  
Volvo VDS-3 VDS-4  
Meets requirements of - MAN M 3271-1 M 3477  
Meets DAF requirements

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral SuperTurbol LA 5W-30

14 Jan 2021

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg

01801-11 55 11

[www.aral-lubricants.de](http://www.aral-lubricants.de)