

SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Aral Vitam DE 68
Product code 456353-DE04
SDS no. 456353
Product type Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

**Use of the substance/
mixture** Hydraulic fluid.
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the supplier of the safety data sheet

Supplier BP Europa SE
 Geschäftsbereich Industrieschmierstoffe
 Erkelenzer Straße 20
 D-41179 Mönchengladbach
 Germany

Telefon: +49 (0)800 7235-074

Aral AG
 Geschäftsbereich Schmierstoffe
 Überseeallee 1
 D-20457 Hamburg

Customer Service Center / Environmental Protection / Product Safety: +49 (0)40 639-52288

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

**EMERGENCY
TELEPHONE NUMBER** Carechem: +44 (0) 1235 239 670 (24/7)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]
 Aquatic Chronic 3, H412

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word No signal word.
Hazard statements H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention P273 - Avoid release to the environment.
Response Not applicable.
Storage Not applicable.
Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label
elements** Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl.
 May produce an allergic reaction.

EU Regulation (EC) No. 1907/2006 (REACH)

Product name Aral Vitam DE 68	Product code 456353-DE04	Page: 1/12
Version 4	Date of issue 25 October 2018	Format Germany (Germany)
		Language ENGLISH

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

Other hazards which do not result in classification Defatting to the skin.
 Note: High Pressure Applications
 Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.
 See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
2,6-ditert-butyl-p-cresol	EC: 204-881-4 CAS: 128-37-0	≤1	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1] [2]
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	REACH #: 01-2119493620-38 EC: - CAS: -	≤0.3	Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	REACH #: 01-2119777867-13 EC: 202-414-9 CAS: 95-38-5	<0.1	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT RE 2, H373 (digestive system, thymus) (oral) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]

See Section 16 for the full text of the H statements declared above.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.

Product name Aral Vitam DE 68	Product code 456353-DE04	Page: 2/12
Version 4	Date of issue 25 October 2018	Format Germany (Germany)
	Language ENGLISH	

SECTION 4: First aid measures

Inhalation	☑ Inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.
---------------------------	--

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Use foam or all-purpose dry chemical to extinguish.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)

5.3 Advice for firefighters

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

For emergency responders Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

6.2 Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections See Section 1 for emergency contact information.
 See Section 5 for firefighting measures.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 12 for environmental precautions.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid contact of spilt material and runoff with soil and surface waterways. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature.

Germany - Storage code 10

7.3 Specific end use(s)

Recommendations See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

<u>Product/ingredient name</u>	<u>Exposure limit values</u>
--------------------------------	------------------------------

SECTION 8: Exposure controls/personal protection

2,6-ditert-butyl-p-cresol

TRGS 900 OEL (Germany).

TWA: 10 mg/m³ 8 hours. Issued/Revised: 9/2012 Form: Inhalable fraction
 PEAK: 40 mg/m³ 15 minutes. Issued/Revised: 9/2012 Form: Inhalable fraction

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.

Our recommendations on the selection of gloves are as follows:

Product name Aral Vitam DE 68	Product code 456353-DE04	Page: 5/12
Version 4	Date of issue 25 October 2018	Format Germany (Germany)
		Language ENGLISH

SECTION 8: Exposure controls/personal protection

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.
 If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.
 It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
 Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.
 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
 Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

- Respiratory protection: EN 529
- Gloves: EN 420, EN 374
- Eye protection: EN 166
- Filtering half-mask: EN 149
- Filtering half-mask with valve: EN 405
- Half-mask: EN 140 plus filter
- Full-face mask: EN 136 plus filter
- Particulate filters: EN 143
- Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Colour	Amber.
Odour	Oily.
Odour threshold	Not available.

Product name Aral Vitam DE 68	Product code 456353-DE04	Page: 6/12
Version 4	Date of issue 25 October 2018	Format Germany (Germany)
		Language ENGLISH

SECTION 9: Physical and chemical properties

pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-21 °C
Flash point	Open cup: 246°C (474.8°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Density	<1000 kg/m ³ (<1 g/cm ³) at 15°C
Solubility(ies)	insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 68 mm ² /s (68 cSt) at 40°C Kinematic: 8.68 mm ² /s (8.68 cSt) at 100°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity estimates

Route	ATE value
Not available.	

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Product name Aral Vitam DE 68	Product code 456353-DE04	Page: 7/12
Version 4	Date of issue 25 October 2018	Format Germany (Germany)
		Language ENGLISH

SECTION 11: Toxicological information

- Inhalation** No specific data.
- Ingestion** No specific data.
- Skin contact** Adverse symptoms may include the following:
irritation
dryness
cracking
- Eye contact** No specific data.
- Delayed and immediate effects as well as chronic effects from short and long-term exposure**
- Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
- Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.
- Skin contact** Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
- Eye contact** Potential risk of transient stinging or redness if accidental eye contact occurs.
- Potential chronic health effects**
- General** No known significant effects or critical hazards.
- Carcinogenicity** No known significant effects or critical hazards.
- Mutagenicity** No known significant effects or critical hazards.
- Developmental effects** No known significant effects or critical hazards.
- Fertility effects** No known significant effects or critical hazards.

SECTION 12: Ecological information

- 12.1 Toxicity**
- Environmental hazards** Harmful to aquatic life with long lasting effects.
- 12.2 Persistence and degradability**
Expected to be biodegradable.
- 12.3 Bioaccumulative potential**
This product is not expected to bioaccumulate through food chains in the environment.
- 12.4 Mobility in soil**
- Soil/water partition coefficient (K_{oc})** Not available.
- Mobility** Spillages may penetrate the soil causing ground water contamination.
- 12.5 Results of PBT and vPvB assessment**
Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
- 12.6 Other adverse effects**
- Other ecological information** Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods**
- Product**
- Methods of disposal** Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
- Hazardous waste** Yes.
- European waste catalogue (EWC)**

Waste code	Waste designation
13 01 10*	mineral based non-chlorinated hydraulic oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

- Packaging**
- Methods of disposal** Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

SECTION 13: Disposal considerations

Waste code	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Special precautions This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)
[Annex XIV - List of substances subject to authorisation](#)
[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

[Other regulations](#)

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b) All components are listed or exempted.

Australia inventory (AICS) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (ENCS) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Product name Aral Vitam DE 68	Product code 456353-DE04	Page: 9/12
Version 4	Date of issue 25 October 2018	Format Germany (Germany)
		Language ENGLISH

SECTION 15: Regulatory information

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Hazardous incident ordinance	Not applicable.
Hazard class for water	1 (classified according AwSV)
Prohibited Chemicals Regulation (ChemVerbotsV)	When placed on the market in Germany, this product is not subject to the Prohibited Chemicals Regulation (ChemVerbotsV).
Occupational restrictions	Observe employment restrictions in the following: Gesetz zum Schutz der arbeitenden Jugend (Jugendarbeitsschutzgesetz – JArbSchG) Gesetz zum Schutz von Müttern bei der Arbeit, in der Ausbildung und im Studium (Mutterschutzgesetz – MuSchG)

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SADT = Self-Accelerating Decomposition Temperature SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Varies = may contain one or more of the following 101316-69-2 / RRN 01-2119486948-13, 101316-70-5, 101316-71-6, 101316-72-7 / RRN 01-2119489969-06, 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN
-----------------------------------	---

Product name Aral Vitam DE 68

Product code 456353-DE04

Page: 10/12

Version 4 **Date of issue** 25 October 2018

Format Germany
(Germany)

Language ENGLISH

SECTION 16: Other information

01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64741-97-5 / RRN
 01-2119480374-36, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN
 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN
 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN
 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN
 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8,
 64742-64-9, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42,
 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 /
 RRN 01-2119474889-13, 74869-22-0 / RRN 01-2119495601-36, 90669-74-2 / RRN
 01-2119970171-43

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

☑ H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373 (oral)	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

☑ Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4
Aquatic Acute 1, H400	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2, H411	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1, H318	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1C, H314	SKIN CORROSION/IRRITATION - Category 1C
Skin Sens. 1, H317	SKIN SENSITISATION - Category 1
STOT RE 2, H373 (oral)	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (oral) - Category 2

History

Date of issue/ Date of revision	25/10/2018.
Date of previous issue	01/03/2018.
Prepared by	Product Stewardship

☑ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Aral Vitam DE 68

Product code 456353-DE04

Page: 12/12

Version 4 **Date of issue** 25 October 2018

Format Germany
(Germany)

Language ENGLISH